

ne Database Setu		Sv	ringe	-	·					ſ
				jcxa reu	rm I Symma	Forma i Mos	minai Voiume	CC) Full	Point	
		ΙΙO		1040 (21)	19	0.5	maig require	181		
<b>1</b> ⊲	+ - /		3CC I		2	1331		31	2.53	
L	<del></del>		SCC I		75	11-		- 5	2.8	
			0CC   0CC		241 2761	131		201	2.17 165 ♥	
		1_15			4.701	101		2U (	1501 🗸	
leedle					Fluid					
Type	Gage	Diameter	Lenath (4	$\overline{\Delta}$	Tvce		Viscosity	Speci	icweicnt 🗳	7
BD-305128	30			3	XI2oav			001 (	0.0002	]
IBD-305136	27	0.02	1 25		IBOOV FIL	Id		1	21	
DB-33333					Asasaa			11		
DD-1234							1	-		
asofsaof	23	23	23	_			1	İ	_	
<u> </u>		L		₹ T	Ш				₹	1
Tube										
	Diameter	Length	Δ							
Tvoe Condore	0.678	0.600	7							
Tupe#1	0.015	54	7							
Tupe#2	0.015		$rac{1}{2}$							
Machine Cor										
	x Force   Zero Adius	Throttle Bac	x TScale Facto		Pegal Zero	Low End	Low Start	Hian Ena	High Start	High Aspirate
Force Travel Ma	40			271 0						

Machine Profile Setup Screen
Set Values for Components of Delivery System
Setup Variable for Machine

FIG. 12A







FIG. 12B










FIG. 17

